2026 EGM Resolution Submission Form for

Class Rules Changes

Submission close: 31st October, 2026

Member Details

Name:	Peter Conde – Chair of VXOICA Technical Committee
Country / National Association:	Australia
Email:	Peterconde@me.com

Resolution Title

Resolution Nov'26 One

Proposed Resolution

That the VX One International Class Association resolves to:

Clarify a range of CRs including documenting items that are already legal by virtue of having been supplied by an LM, but where this is not widely known. The rules impacted are:

- C.4.1(b)
- C.9.9 (b) (12)
- C.9.9 (b) (19)
- C.9.9 (b) (23)
- G.3.5
- G.4.2 (e)

The revised wording is in the tables below and further information is in a separate document to this resolution showing existing wording in full, this proposed new wording and articulation of Rationale/ Issues/ Pros/ Cons

Class Rule	Proposed Wording
C.4.1 (b)	(B) The Bow Number shall be placed *on both sides of the hull* as per below: (1) Top edge parallel to and 65-75 mm below the cut edge of the gunwale. (2) Leading edge 150-160 mm behind the bow stem
C.9.9 (b) (12)	C.9.9 RUNNING RIGGING (b) MODIFICATIONS, MAINTENANCE AND REPAIR (12) Cleats, parts or equipment may be replaced provided that the replacement is of similar weight, size or type and performs the same function. *Gennaker cleats may be replaced with smaller cleats.* Replacement parts or equipment may be obtained from any supplier.
C.9.9 (b) (19)	C.9.9 RUNNING RIGGING (b) MODIFICATIONS, MAINTENANCE AND REPAIR (19) Outhaul purchase maximum 4:1 as supplied by the builder. *The outhaul attachment to the mainsail clew may include a shackle or hook and friction ring or single block.*
C.9.9 (b) (23)	C.9.9 Running Rigging (b) MODIFICATIONS, MAINTENANCE AND REPAIR *(23) The Cunningham system may comprise up to 6:1 primary purchase system, and maybe doubled at the mainsail eye provided that no additional fixings/ attachment points are made to the hull or spars.*
G.3.5	G.3.5 MAINSAIL DIMENSIONS (in table, row 13) The centreline of batten pocket 2 shall be below the upper leech point, *which is 820mm below the **aft head point***
G.4.2 (e)	The following are permitted: stitching, glues, tapes, webbing, **corner** eyes or pressed ring, *clew board*, **batten pocket** elastic, **batten pocket patches**, **batten pocket** end caps, **leech** line with cleat, *foot line with cleat*, **windows**, tell tales, **sail** shape indicator stripes

Rationale

Clearer and more consistent understanding of what is required and what is permitted in the CR

Impact Assessment

Strategic Impact:	Clearer Class Rules, less ambiguity on what is permitted.
Financial Impact:	Nil
Governance / Rule Change:	☐ **Yes** ☐ No
Requires Constitutional Amendment:	☐ Yes ☐ **No**